C.O.I. COMPAGNIA OTTICA ITALIANA srl

Via Paganini, 10 - 20131 MILANO tel. (++39) 02 29526650/0229526651

E-Mail: <u>info@coivision.com</u> www.coivision.com

PACP-8000- AUTO CHART PROJECTOR Cod. 51.002.00

Product description and data sheet

Eyesight measurement using diversified charts

Diversified charts (4 types of A/C/D/R) per country are retained including binocular balance, aniseikonia, stereopsis, binocular vision test chart

Cost saving through adoption of LED light source

Maintenance & repair costs can be saved through adoption of LED light source having a semi-permanent service life

Bright & clear chart display

Brighter & clear chart display is provided by adoption of white LED

Refined design

Optometry room is made to stand out by the refined design embodying an eyeball.

Compact size

A roomy optometry space is provided using a more compact size

- Size: 25% Reduction comparing with PACP-7000

- Weight: 25% lighter than PACP-7000

Convenient focus adjustment

Convenient focus adjustment is enabled by a rotary aperture.

Charts	42 EA
Distance of Projector	2.5~8m (8m distance projection screen is optional)
Chart magnification	30× (when projected at 5m distance)
Lamp	LED lamp
Chart rotation speed	average 0.3 sec
Power save	11 minutes (after last signal)
Tilt angle	± 20 degrees
Resolution	50 lines / mm
Program	2 programs with a maximum of 40 charts each
Power Supply	100 - 240V~, 50/60Hz
Power consumption	60VA
Dimensions	Body (Exclude Stand): 200(W)×290(D)×172(H) mm
	Body (Include Stand): 200(W)×290(D)×235(H) mm
*** * 1.4	Remote Controller: 64(W)×196(D)×20(H) mm
Weights	Body: 3.58 kg(Stand included)
	Remote Controller: 160 g (Battery included)
Standard Accessories	Screen, Remote Controller, Table Stand, Dust Cover,
	Power Cable, T wrench, Fuse, Battery
Optional Accessories	Red/Green glasses, Polarization glasses



REGULATION (EU) 2017/745 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

CND: Z1212012099

BD/RDM: 355905